

17" All-in-one Touchcomputer

Model: KTP-0170US-SA4BW



Keetouch 17" All-in-one Touchcomputer, designed, developed and built to provides an attractive ultra-compact 17" touch solution that can fit virtually anywhere in any point-of-service environment. It packs Keetouch's quality and reliability into an integrated, affordable touchcomputer

◆ Main Features

- ◆ Space saving and "Designed for touch" features such as a stable tilt base
- ◆ One Ethernet, one serial, one LPT and four high-speed USB 2.0 ports for maximum expansion. In addition, optional USB Hub with 4 ports output
- ◆ Dual RS232 and USB touch interface
- ◆ Available with SAW or Infrared touch
- ◆ Mounting holes on the base bottom for tabletop security
- ◆ Finger or gloved hand operation

◆ Applications

- ◆ Point-of-sale (POS)
- ◆ Point of service
- ◆ Kiosk
- ◆ Point-of-interest

Shenzhen KeeTouch Electronic Co., Ltd.

www.keetouch.com

◆ Specification

Case/bezel color	Dark gray	
Processor	Intel (R) Atom (TM) CPU 330 @1.60GHz(ES)	
Mainboard	Intel D945GCLF2	
Memory (RAM)	1GB DDR2 standard ,Expandable	
Serial Port	1 x RS232 serial	
USB Port	4 x 2.0 USB, In addition,optional USB Hub with 4 ports output	
Ethernet 100/10Base-T Port	1 x LAN RJ45	
LPT	1 x LPT	
Audio port	audio-out,mic-in	
Hard Drive	1 x 2.5"160 GB SATA hard drive	
LCD Type	Active matrix TFT-LCD	
Display Size	17 " (diagonal)	
Active Area	13.3 " (338mm)×10.6 " (270mm)	
Suggested Resolution	1280×1024	
Support Colors	16.2M	
Brightness(Typ.)	Pure LCD Panel	300cd/m ²
	With Touch Glass Sensor	270cd/m ²
Response Time(Typ.)	5ms	
Viewing Angle (Typ.at CR>10)	Horizontal(left/right)	80°/80°
	Vertical(up/down)	80°/80°
Contrast Ratio(Typ.)	500:1	
LCD Back light Life(Typ.)	50,000 Hours	
Tilt Adjust	From 0° to 75°	
Touchcomputer Dimensions with Stand	Width: 455mm Height: 400mm Depth:270mm	
OSD Control	Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset	
Touch screen Type	Keetouch 17" SAW or Infared touchscreen	
Touch System Interface	Dual RS232 and USB	
Regular Warranty	3 years; except for LCD panel 1 year	
Power Supply	Computer: External brick; Input (line) voltage: 100-240 VAC, 50-60 Hz; Output voltage/current: 19 V at3.42 A	
	Monitor: Internal brick in base; Input (line) voltage: 100-240 VAC, 50-60 Hz	
Other features	threaded holes on bottom of base for secure mounting	
Environment	Operating Temp.	0~40°C
	Storage Temp.	-20~60°C
	Operating RH:	20%~80%
	Storage RH:	5%~95%
NOTE:The SPEC. will change follow the LCD panel and computer system configure		

